

Mayflower®-SII-Q670E

High quality 19" 4U system for demanding industrial applications in harsh environments

Features

- ↗ High-Performance with Intel® Core™ i CPUs 12th/13th/14th Generation
- ↗ Capable for complex system configurations
- ↗ Up to 7x PCIe slots for expansion cards
- ↗ Robust full industrial components for 24/7 operation
- ↗ Drive cages in anti-vibration design, hold-downs clamps and washable air filters

Configuration example

Further configurations on request!

Mainboard:

Industrial Mainboard (ATX)
24/7 operation, long-term available

Processor:

Intel® Core™ i 12th/13th/14th Generation
Chipset: Intel® Q670E

Memory:

4x DDR4 DIMM, max. 128GB

Graphic:

Onboard Intel® UHD 730/770
(depending on CPU)

Drive Bays:

Internal
1x M.2 (M-key, type:2280)
3x 3.5"
External
3x 5.25", 1x 3.5"

Environment:

Operating Temperature
0° ~ 50° C
Storage Temperature
-40° ~ 85° C
Relative Humidity (operation)
0 ~ 95 % (non condensing)

Power Supply:

90 ~ 264 VAC, 500 Watt, 80 Plus
On request: Redundant power supplies for AC and DC

Expansions:

1x PCIe x16 (Gen 4), full height
1x PCIe x8 (Gen 3), full height
3x PCIe x4 (Gen 3), full height
2x PCI, full height

Mechanical:

Chassis
19 inch 4U rackmount chassis
Dimensions (W x H x D)
430 x 176 x 465 mm
Cooling
Active, 1x 120 mm fans

I/O:

Back
2x GBit LAN (RJ45)
2x USB 3.2 (Gen 2)
2x USB 3.2 (Gen 1)
4x USB 2.0
1x RS-232
1x DisplayPort
1x HDMI
1x VGA
2x Audio (Line-Out, Mic)
Front
2x USB 2.0
Internal
2x USB 2.0 type A
1x GPIO Header (8 Bit)

Operating System:

Microsoft® Windows® 10/11, Linux®

Features:

Watchdog Timer
Intel® vPro, AMT & TPM support

*Ambient temperature at full expansion at full load in 24/7 operation: 0°~40°C



Mayflower®-SII-Q670E

Additional illustrations



Rear view



Front view (open)

InoNet Competences and Services



Consulting



Development



Testing



Customization



Manufacturing



Certifications

InoNet Computer GmbH
Wettersteinstraße 18
82024 Taufkirchen, Germany
www.inonet.com